



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Cirrus Suspension Wall Wash with Left Feed is a linear LED fixture that features a wall wash lens for a smooth and uniform beam spread. Available in various increments from 36 to 288 inches, a variety of finish options, two wattage options, and a spectrum of color temperature options. Chrome finish available up to 84 inch length. Product is built to order. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Includes a 4 inch round canopy and adjustable 12 foot coaxial and aircraft cables. Additional aircraft cables are included for support when fixture exceeds 72 inches. Power feeds at left (when viewing wall to be washed) or you may adjust to center within 5 feet of either end.



Shown in: Satin Aluminum / White Lens



SHADE COLOR	White Lens
BODY FINISH	Satin Aluminum
WATTAGE	21W
DIMMER	Dimmable
DIMENSIONS	36"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE	
LAMP	3 x LED/7W/24V LED

Technical Information

LUMINOUS FLUX	1122 lumens
LUMENS/WATT	160.29
LAMP COLOR	2700K
COLOR RENDERING	95 CRI

SPEC # EDG684079

Shown with 4 inch square canopy



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE