

Lightology

lightology.com
866-954-4489
12-28-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG684586**
Approved On: _____ Approved By: _____

Cirrus D1 HE Linear Suspension w/Remote Power End Feed

By PureEdge Lighting



Description

The Cirrus High Efficiency Remote Power D1 Lens Linear Downlight Suspension with End Feed and Round or Square Canopy is a linear LED fixture that offers direct light in a clean, contemporary style. Available in various increments from 36 to 420 inches with a 100 degree white diffused D1 direct downlight lens, four wattage options, a variety of finishes, and a spectrum of color temperature options. Chrome finish available up to 84 inch length. Includes a 4 inch round or square canopy and adjustable 12 foot coaxial and aircraft cables. Additional aircraft cables are included for support when fixture exceeds 72 inches. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Title 24 compliant when used with 2700K color temperature and a Universal power supply. Product is built to order.

Specifications


COLOR White Lens
BODY FINISH Satin Nickel
WATTAGE 6W
DIMMER Dimmable
DIMENSIONS 36"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE 3 x LED/2W/24V LED

Technical Information

LAMP LIFE 50000 hours
COLOR RENDERING 95 CRI
LAMP COLOR 2700K
LUMENS/WATT 223.50
LUMINOUS FLUX 447 lumens



Shown in satin nickel / white lens



CLICK TO VIEW PRODUCT

Notes: