

# Lightology

lightology.com  
866-954-4489  
07-06-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **EDG684586**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Cirrus D1 HE Linear Suspension w/Remote Power End Feed By PureEdge Lighting



### Description

The Cirrus High Efficiency Remote Power D1 Lens Linear Downlight Suspension with End Feed and Round or Square Canopy is a linear LED fixture that offers direct light in a clean, contemporary style. Available in various increments from 36 to 420 inches with a 100 degree white diffused D1 direct downlight lens, four wattage options, a variety of finishes, and a spectrum of color temperature options. Chrome finish available up to 84 inch length. Includes a 4 inch round or square canopy and adjustable 12 foot coaxial and aircraft cables. Additional aircraft cables are included for support when fixture exceeds 72 inches. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Title 24 compliant when used with 2700K color temperature and a Universal power supply. Product is built to order.

### Specifications


COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	6W
DIMMER	Dimmable
DIMENSIONS	36"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE	3 x LED/2W/24V LED

### Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	2700K
LUMENS/WATT	223.50
LUMINOUS FLUX	447 lumens



Shown in satin nickel / white lens



CLICK TO VIEW PRODUCT

Notes: