

lightology.com 866-954-4489 08-04-25

Project:	Project:													
Company:														
Location:	Fixture Type:													
SPEC #: EDG687466														
Approved On:	Approved By:													

Cirrus D1 Warm Dim Suspension w/Remote Power End Feed By PureEdge Lighting







Description

The Cirrus Remote Power D1 Lens Warm Dim Linear Downlight Suspension with End Feed and Round or Square Canopy is a linear LED fixture that offers direct light in a clean, contemporary style. Available in various increments from 36 to 240 inches with a diffused white 100 degree beam spread lens or 60 degree clear frosted lens, optional black or white louver, a variety of finishes, 5 LED watts per foot, and Warm Dim 2700K to 2000K (27D) or 3000K to 2000K (30D) color temperature. Chrome finish available up to 84 inch length. Includes a 4 inch round or square canopy and adjustable 12 foot coaxial and aircraft cables. Additional aircraft cables are included for support when fixture exceeds 72 inches. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Title 24 compliant when used with 2700K color temperature and a Universal power supply.Product is built to order.

Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE

Technical Information

LAMP LIFE .															50	000) ho	ours	;
COLOR REND	ERING																95	CR	I
LAMP COLOR												2	270	001	ΚV	Var	m [Dim	ı
LUMENS/WAT	т																14	1.60)
LUMINOUS FL	UX .														70)8 I	um	ens	5



Shown in satin nickel / white lens





CLICK TO VIEW PRODUCT

Notes:			