

# Lightology

lightology.com  
866-954-4489  
02-12-26

Project:

Company:

Location:

Fixture Type:

SPEC #: **EDG687466**

Approved On:

Approved By:

## Cirrus D1 Warm Dim Suspension w/Remote Power End Feed

By PureEdge Lighting



### Description

The Cirrus Remote Power D1 Lens Warm Dim Linear Downlight Suspension with End Feed and Round or Square Canopy is a linear LED fixture that offers direct light in a clean, contemporary style. Available in various increments from 36 to 240 inches with a diffused white 100 degree beam spread lens or 60 degree clear frosted lens, optional black or white louver, a variety of finishes, 5 LED watts per foot, and Warm Dim 2700K to 2000K (27D) or 3000K to 2000K (30D) color temperature. Chrome finish available up to 84 inch length. Includes a 4 inch round or square canopy and adjustable 12 foot coaxial and aircraft cables. Additional aircraft cables are included for support when fixture exceeds 72 inches. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Title 24 compliant when used with 2700K color temperature and a Universal power supply. Product is built to order.

### Specifications


COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	36" L x 0.9" W x 0.9" H
INTEGRATED LED MODULE	3 x LED/5W/24V LED

### Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	2700K Warm Dim
LUMENS/WATT	141.60
LUMINOUS FLUX	708 lumens



Shown in satin nickel / white lens



CLICK TO VIEW PRODUCT

Notes: