

Lightology

lightology.com
866-954-4489
04-24-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG695026**
 Approved On: _____ Approved By: _____

Cirrus R1 Linear Suspension w/Remote/End Feed/RD Canopy

By PureEdge Lighting



Description

The Cirrus R1 Lens End Feed Suspension with Remote 24VDC Power Supply (sold separately) and Round Canopy is a linear LED fixture that offers direct light in a clean, contemporary style. Features a diffused white rectangular lens with a 140 degree beam spread available in various increments from 36 to 420 inches, a variety of finishes, four wattage options, and a spectrum of color temperature options. Product is built to order. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Includes a 4 inch round canopy and adjustable 12 foot coaxial and aircraft cables. Additional aircraft cables are included for support when fixture exceeds 96 inches.

Specifications


COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	21W
DIMMER	Dimmable
DIMENSIONS	36"L x 0.9"W x 1.46"H
INTEGRATED LED MODULE	3 x LED/7W/24V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	2700K
LUMENS/WATT	198.00
LUMINOUS FLUX	1386 lumens



Shown in satin nickel / white lens



CLICK TO VIEW PRODUCT

Notes: