



BRAND

PureEdge Lighting

DESCRIPTION

Soft Line Indirect LED Lighting System provides soft, ambient, indirect illumination for decorative and architectural applications. For compact shipment and storage, Soft Line coils like a retractable tape measure. When uncoiled, the Soft Line becomes a 1.25 inch wide cupped, rigid aluminum channel that can be mounted on any angle between opposing wall, ceiling or floor surfaces. Soft Line is field-cuttable. Soft Line features a single row of 24 volt Soft Strip in 2700K, 3000K, 3500K, 4000K or 5700K color temperature. Includes Soft Line channel, a pair of power feed and non-power feed turnbuckles and a single row of LED Soft Strip. Soft Line 24 inch standoff, sold separately. Turnbuckles support Soft Line on any angle from 0-60 degrees, feed power from one end and mount to a standard 4 inch square electrical box with round plaster ring. Turnbuckles may be reversed and mounted (opposite the power feed) to a ceiling, wall or floor. Lengths over 20 feet require power feed at both ends. System is powered by a remote Universal (UNI) or Lutron Hi-Lume power supply sold separately. ETL listed. Title 24 compliant when used with a Universal (UNI) power supply. Power supply, standoff, and controller sold separately.



| | |
|-----------------------|---------------------|
| SHADE COLOR | N/A |
| BODY FINISH | Satin Aluminum |
| WATTAGE | 25W |
| DIMMER | Dimmable |
| DIMENSIONS | 120"L x 1.25"W |
| INTEGRATED LED MODULE | |
| LAMP | 1 x LED/25W/24V LED |

Technical Information

| | |
|-----------------|-------------|
| LUMINOUS FLUX | 2890 lumens |
| LUMENS/WATT | 115.60 |
| LAMP COLOR | 3000K |
| COLOR RENDERING | 95 CRI |

| | |
|--------|----------|
| SPEC # | EDG69723 |
|--------|----------|

| COMPANY | PROJECT | FIXTURE TYPE | APPROVED BY | DATE |
|---------|---------|--------------|-------------|------|
| | | | | |