

lightology.com 866-954-4489 12-28-25

Project:	
Company:	
Location:	Fixture Type:
Location.	Fixture Type:
SPEC #: EDG711918	
Approved On:	Approved By:

Nova Up/Down Warm Dim Suspension w/Center Feed Power By PureEdge Lighting







Description

Nova Up/Down Warm Dim Suspension with Center Feed Power is a linear LED suspension offering direct and indirect light in a clean and contemporary architectural style. Downlight features a diffused white lens with 100 degree beam spread or a clear frosted lens with a 60 degree beam spread. The uplight features a clear frosted 60 degree lens. Both the up and downlight can be dimmed together or independently. Available in various increments from 36 to 120 inches, a variety of finishes, 10 LED watts per foot (5 up/5 down), an optional black or white louver, and Warm Dim 2700K to 2000K (27D) or 3000K to 2000K (30D) color temperature. Fixture includes adjustable 12 foot aircraft suspension cables and a linear rectangle canopy. Fixtures over 72 inch in length include two additional aircraft cables for support.Includes a 120V input/24VDC output Universal (UNI) power supply inside canopy. Dimmable with an electronic low voltage (ELV), Triac (magnetic), or 0-10V dimmer, sold separately. Note: Product is built to order.

Specifications


COLOR
BODY FINISH Satin Nickel
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE

Technical Information

LAMP LIFE	 	 	. 50000 hours
COLOR RENDERING	 	 	95 CRI
LAMP COLOR	 	 2'	700K Warm Dim
LUMENS/WATT	 	 	170.70
LUMINOUS FLUX .	 	 	1707 lumens



Shown in satin nickel / white lens





CLICK TO VIEW PRODUCT

Notes:	