

lightology.com 866-954-4489 12-09-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG713020	
Approved On:	Approved By:

Nova Up/Down Warm Dim Suspension w/Remote Power/RD Canopy By PureEdge Lighting







Description

Nova Warm Dim Remote Power Up/Down Suspension with Round Canopy End Feed is a linear LED fixture that offers both direct and indirect light in a clean, LED dot-free smooth line of light in a contemporary style. Nova is available in various increments from 36 to 240 inches and features a diffused white 100 degree or clear frosted 60 degree downlight lens, clear frosted 60 degree uplight lens, optional black or white louver for 100 degree downlight lens, multiple finishes, 10 LED watts per foot, and Warm Dim 2700K to 2000K (27D) or 3000K to 2000K (30D) color temperature. 84 inch maximum length for Chrome finish. ETL listed. Title 24 compliant when used with Universal (UNI) power supply. Fixture includes a 5 year warranty. Product is built to order. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Includes a 4 inch round canopy and adjustable 12 foot coaxial cables (additional aircraft cables included for support when fixture exceeds 72 inches).

Specifications


COLOR	ns
BODY FINISH	кel
WATTAGE	W
DIMMER Low Voltage Electron	nic
DIMENSIONS	"H
INTEGRATED LED MODULE	Ð

Technical Information

LAMP LIFE		 	 50000 hours
COLOR RENDERIN	G	 	 95 CRI
LAMP COLOR		 	 2700K Warm Dim
LUMENS/WATT .		 	 170.70
I UMINOUS FI UX		 	 1707 lumens



Shown in satin nickel / white lens





CLICK TO VIEW PRODUCT