



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

The Cirrus Power D1 Lens Warm Dim Linear Downlight Suspension with Center Feed, with or without a Fast Jack (FJ) Port, is a linear LED fixture that offers direct light in a clean, contemporary style. Available in various increments from 36 to 420 inches with a 100 degree white diffused or 60 degree clear frosted direct downlight lens, optional black or white louver, a variety of finishes, 5 LED watts per foot, and Warm Dim 2700K to 2000K (27D) or 3000K to 2000K (30D) color temperature. Chrome finish available up to 84 inch length. Satin Black finish features Antique Bronze hardware. All other finishes feature Satin Nickel hardware. Includes a linear canopy with 120V/24VDC Universal (UNI) LED power supply and 12 foot adjustable coaxial cables. Additional aircraft cables provided for support when fixture exceeds 72 inches. Fixture lengths over 96 inches ship in two segments. Cirrus is dimmable with an electronic low voltage (ELV), Triac (magnetic), or 0-10V dimmer, sold separately. Fast Jack port (C1) includes an electronic low voltage power supply, dimmable with an electronic low voltage (ELV) dimmer, sold separately. ETL listed. Suitable for damp locations. Title 24 compliant. Fixture includes a 5 year warranty. Product is built to order. Fast Jack head required for C1 option, sold separately.




Shown in: Satin Nickel / White Lens

SHADE COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	36"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE	
LAMP	3 x LED/5W/24V LED

Technical Information

LUMINOUS FLUX	708 lumens
LUMENS/WATT	141.60
LAMP COLOR	2700K Warm Dim
COLOR RENDERING	95 CRI

SPEC # EDG721630



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE