

Lightology

lightology.com
866-954-4489
04-29-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **EDG747408**

Approved On: _____ Approved By: _____

Zipp Wave Linear Suspension with Remote Power By PureEdge Lighting



Description

Add angles and dimensions to any space with the Zipp Wave Suspension Downlight with End Feed Canopy. Available with a round or square canopy in a range of increments from 48 to 240 inches and features a white lens with 100 degree beam spread, optional adjustable white or black louver, multiple finishes, and a spectrum of color temperatures. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply up to 100 watts at a maximum of 40 feet away. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Includes one 4.6 inch round or square canopy and 12 foot adjustable coaxial cables. Lengths over 96 inches ship as two segments.

Specifications


COLOR White / Black Louver
BODY FINISH Satin Nickel
WATTAGE 20W
DIMMER Low Voltage Electronic
DIMENSIONS 48"L x 0.7"W x 0.7"H
INTEGRATED LED MODULE 4 x LED/5W/24V LED

Technical Information

LAMP LIFE 50000 hours
COLOR RENDERING 95 CRI
LAMP COLOR 2700K
LUMENS/WATT 65.60
LUMINOUS FLUX 328 lumens



Shown in satin nickel / white / black louver



CLICK TO VIEW PRODUCT

Notes: