

Lightology

lightology.com
866-954-4489
08-26-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG759278**
Approved On: _____ Approved By: _____

Zipp Linear Suspension with End Feed Power

By PureEdge Lighting



Description

Zipp Downlight Suspension with Power is a linear LED fixture that features even, direct light without LED spots. Zipp is available with one or two canopies in various increments from 36 to 480 inches and features a diffused white lens with 100 degree beam or clear frosted lens with 60 degree beam, optional black or white louver, a variety of finishes, three wattage options, and a spectrum of color temperature options. Warm Dim includes 5 LED watts per foot available in 2700K-2000K (27D) and 3000K-2000K (30D) color temperature. Unlike standard LEDs, Warm Dim LEDs are designed to shift to a warmer color temperature as they are dimmed, replicating the effects of incandescent and halogen light sources. 84 inch maximum length for Chrome finish. Supplied with adjustable 12 foot coaxial and aircraft cables. Includes one or two square end feed canopies which mounts to a standard junction box with a 120V/24VDC electronic low voltage LED power supply. Power supply wattage and canopy option dependent on length of fixture. Dimmable with an electronic low voltage dimmer, sold separately. Fixture includes a 5 year warranty. Optional accessories and dimmer control sold separately. Product is built to order. Note: Warm Dim available in 5 watt option only.

Specifications


COLOR White Lens
BODY FINISH Satin Nickel
WATTAGE 6W
DIMMER Low Voltage Electronic
DIMENSIONS 36"L x 0.7"W x 0.7"H
INTEGRATED LED MODULE 3 x LED/2W/24V LED

Technical Information

COLOR RENDERING 95 CRI
LAMP COLOR 2700K
LUMENS/WATT 147.00
LUMINOUS FLUX 294 lumens



Shown in satin nickel / white lens



| CANOPY CHART | | |
|--------------|---|---------------------------------------|
| VERSION | 8" x 4" FLOOR CANOPY (60 WATTS MAX @ 50 WATTS LED) | 6" SURFACE MOUNT CANOPY (60 WATTS) |
| 2W Lengths | 16" to 240" | 24" to 480" |
| 5W Lengths | 16" to 120" | 12" to 240" |
| 7W Lengths | 16" to 80" | 8" to 160" |



CLICK TO VIEW PRODUCT

Notes: