

Lightology

lightology.com
866-954-4489
05-25-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC768215**
 Approved On: _____ Approved By: _____

Aether 2IN Round Adjustable Downlight Trim By WAC Lighting



Description

Aether 2 inch Round LED Shallow Housing Downlight Trim was designed to fit in tight plenum spaces with complex HVAC ducts, sprinkler pipes, and conduit runs without sacrificing lumen output. Die-cast aluminum trim with extruded aluminum heat sink. 2 inch trim aperture and housing height. 35 degree cut-off angle. 0-25 degree vertical and 360 degree horizontal adjustment. Dimmable to 0% with 0-10V dimmers (120 & 277V) or to 10% with low-voltage electronic dimmers (120V only). Choice of 85 or 90 CRI; 2700K, 3000K, 3500K, or 4000K color temperature; and 40 degree (flood) or 26 degree (narrow flood) beam angle. Accommodates ceiling thickness of 0.5-1 inches. 5 year WAC Lighting warranty. UL listed. Energy Star. Suitable for wet locations. NOTE: A complete fixture requires a housing and trim, sold separately. Note: 90CRI option is only available in 2700K and 3000K.

Specifications



REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	4.13"W x 2"H
INTEGRATED LED MODULE	1 x LED/15W/120-277V LED

Technical Information

APERTURE SIZE	2.000"
APERTURE SHAPE	Round
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	26°
COLOR RENDERING	85 CRI
LAMP COLOR	2700K
LUMENS/WATT	86.33
LUMINOUS FLUX	1295 lumens



Shown in white



CLICK TO VIEW PRODUCT

Notes: