

# Lightology

lightology.com  
866-954-4489  
12-28-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **WAC768257**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Aether 2 inch Round Trimless Downlight Trim By WAC Lighting



### Description

Aether 2 Inch Round Trimless (invisible) Downlight was designed to fit in tight plenum spaces with complex HVAC ducts, sprinkler pipes, and conduit runs. Die-cast aluminum trim with extruded aluminum heat sink. Available in Brushed Nickel, White, Haze or Black. Dimmable to 0% with 0-10V dimmers (120 & 277V) or to 10% with low-voltage electronic dimmers (120V only). Choice of 85 or 90 CRI; 2700K, 3000K, 3500K, or 4000K color temperature; and 17 degree (spot), 24 degree (narrow flood), 40 degree (flood), or 50 degree (wide flood) beam angle. 35 degree cutoff angle for downlight. 2 inch trim aperture and housing height. Accommodates ceiling thickness of 0.5-1 inch. 5 year WAC Lighting warranty. UL listed for wet locations. Title 24 Compliant. A complete fixture includes a housing and trim, sold separately. Note: 90CRI option is only available in 2700K and 3000K.

### Specifications



REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	5.88"W x 2"H
INTEGRATED LED MODULE	1 x LED/15W/120V LED

### Technical Information

APERTURE SIZE	2.000"
APERTURE SHAPE	Round
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	17°
COLOR RENDERING	85 CRI
LAMP COLOR	2700K
LUMENS/WATT	82.00
LUMINOUS FLUX	1230 lumens



Shown in black



CLICK TO VIEW PRODUCT

Notes: