

# Lightology

lightology.com  
866-954-4489  
12-28-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG77296**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## RGB 100W 24VDC LED Power Supply

By PureEdge Lighting



### Description


The PSB-100W-24VDC-RGB Class 2 LED Power Supply accepts input voltage in a range of 120-277 volts AC and outputs 24 volts DC power up to 100 watts. The integrated RGB driver receives signals from CDP, CTP, CDMX1-RGBW or CDMX1-2XK to control RGB color mixing and light intensity. Features short circuit and overload protection. For indoor applications only. To avoid overheating the power supply, install it in a ventilated remote location where air flows. Maintain proper spacing among power supplies when multiple power supplies are installed in the same remote location. Power Input: 120-277VAC, 50/60Hz. Power Output: Class 2, 24VDC, 4.16A, 100 watts maximum. Compatible Controllers: Touch Screen Controller with Power Supply (CTP), Color Dial Controller with Power Supply (CDP), DMX 1-Zone RGBW Touch Controller (CDMX1-RGBW), or Tunable White Touch Controller (CDMX1-2XK), sold separately. ETL listed. 12.15 inch width x 6.48 inch depth x 2.18 inch height.

### Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	100W
DIMMER	Dimmable
DIMENSIONS	12.15"W x 2.18"H x 6.48"D
BULB NOT INCLUDED	N/A



Shown in white



CLICK TO VIEW PRODUCT

Notes: