

# Lightology

lightology.com  
866-954-4489  
12-28-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG782865**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Pix Sticks Cirrus D1 Lens Suspension with Power

By PureEdge Lighting



### Description

The Pix Sticks Cirrus Suspension with D1 Direct Lens is a customizable chandelier for the modern home, office, restaurant, or commercial area. Features linear channels that intersect at alternate heights casting downlight illumination through diffused white lenses. Available in a variety of finishes, a spectrum of color temperature options including Warm Dim, and 5 LED watts per foot per channel. Includes three, five or seven sticks between 39-120 inches in length. Satin Nickel, Chrome and White finishes supplied with matching canopy and Satin Nickel wires. Antique Bronze and Satin Black finishes supplied with a Black canopy and Black wires. Supplied with a metal canopy (12 inch for 3 and 5-stick and 16 inch for 7-stick), a 120 volt input, 24VDC Class 2 output electronic low voltage LED power supply, and 12 feet of suspension cable. Dimmable with an electronic low voltage dimmer: (recommended: Lutron Diva DVCLV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, and Lutron Radio Ra 2, or Legrand Adorne ADTP703TU), sold separately. Product is built to order.

### Specifications


COLOR . . . . . White Lens  
BODY FINISH . . . . . Satin Nickel  
WATTAGE . . . . . 60W  
DIMMER . . . . . Low Voltage Electronic  
DIMENSIONS . . . . . 48"L x 0.9"W x 0.9"H  
INTEGRATED LED MODULE . . . . . 12 x LED/5W/24V LED

### Technical Information


LAMP LIFE . . . . . 50000 hours  
COLOR RENDERING . . . . . 92 CRI  
LAMP COLOR . . . . . 2700K  
LUMENS/WATT . . . . . 648.00  
LUMINOUS FLUX . . . . . 3240 lumens



Shown in satin nickel / white lens



D1 - Direct 0.9" Lens



CLICK TO VIEW PRODUCT

Notes: