

# Lightology

lightology.com  
866-954-4489  
04-25-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **EDG783011**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Pix Sticks Cirrus D1 Lens Warm Dim with Power

By PureEdge Lighting



### Description

The Pix Sticks Warm Dim Cirrus Suspension with D1 Direct Lens is a customizable chandelier for the modern home, office, restaurant, or commercial area. Features linear channels that intersect at alternate heights casting downlight illumination through diffused white lenses. Available in Warm Dim 2700K and 3000K color temperatures, allowing you to dial in the familiar glow of a dim incandescent or halogen light to 2000K, and 5 LED watts per foot per channel. Includes three, five or seven sticks between 39-120 inches in length. Satin Nickel, Satin Black and White finishes supplied with matching canopy. Antique Bronze and Chrome finishes supplied with a Black canopy and wires. Supplied with a metal canopy (12 inch for 3 and 5-stick and 16 inch for 7-stick), a 120 volt input, 24VDC Class 2 output electronic low voltage LED power supply, and 12 feet of suspension cable. Dimmable with an electronic low voltage dimmer: (recommended: Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, and Lutron Radio Ra 2, or Legrand Adorne ADTP703TU), sold separately. Product is built to order.

### Specifications



COLOR . . . . . White Lens  
 BODY FINISH . . . . . Satin Nickel  
 WATTAGE . . . . . 60W  
 DIMMER . . . . . Low Voltage Electronic  
 DIMENSIONS . . . . . 48"L x 0.9"W x 0.9"H  
 INTEGRATED LED MODULE . . . . . 12 x LED/5W/120V LED

### Technical Information

LAMP LIFE . . . . . 50000 hours  
 COLOR RENDERING . . . . . 92 CRI  
 LAMP COLOR . . . . . 2700K Warm Dim  
 LUMENS/WATT . . . . . 566.40  
 LUMINOUS FLUX . . . . . 2832 lumens



Shown in satin nickel / white lens



CLICK TO VIEW PRODUCT

Notes: