

# Lightology

lightology.com  
866-954-4489  
12-30-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG783211**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Pix Sticks Cirrus D1 Lens Warm Dim with Remote Power

By PureEdge Lighting



### Description

The Pix Sticks Cirrus Warm Dim Suspension with D1 Direct Lens is a customizable chandelier for the modern home, office, restaurant, or commercial area. Features linear channels that intersect at alternate heights casting downlight illumination through diffused white lenses. Available in a variety of finishes, includes 5 watts per foot per channel, and Warm Dim 2700K-2000K (27D) and 3000K-2000K (30D) color temperature options. Unlike standard LEDs, Warm Dim LEDs are designed to shift to a warmer color temperature as they are dimmed, replicating the effects of incandescent and halogen light sources. Includes three, five or seven sticks between 39-96 inches in length. ETL listed. Suitable for damp locations. Title 24 compliant. Product is built to order. Note: Requires a 24VDC remote Universal (UNI) power supply. Includes a metal canopy (12 inch for 3 and 5-stick and 16 inch for 7-stick), and 12 feet of suspension cable. Remote power supply and dimmer control sold separately. Note: Channel finishes in Satin Nickel, Satin Black, Chrome, Antique Bronze or White. Satin Nickel and White finishes supplied with matching canopy and hardware. Satin Black, Antique Bronze and Chrome finishes supplied with a Black canopy.

### Specifications


COLOR . . . . . White Lens  
BODY FINISH . . . . . Satin Nickel  
WATTAGE . . . . . 100W  
DIMMER . . . . . Low Voltage Electronic  
DIMENSIONS . . . . . 48"L x 0.9"W x 0.9"H  
INTEGRATED LED MODULE . . . . . 20 x LED/5W/24V LED  
COUNTRY OF ORIGIN . . . . . United States

### Technical Information


LAMP LIFE . . . . . 50000 hours  
COLOR RENDERING . . . . . 92 CRI  
LAMP COLOR . . . . . 2700K Warm Dim  
LUMENS/WATT . . . . . 944.00  
LUMINOUS FLUX . . . . . 4720 lumens



Shown in satin nickel / white lens



D1 - Direct 0.9" Lens



CLICK TO VIEW PRODUCT

Notes: