

# Lightology

lightology.com  
866-954-4489  
12-28-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG797357**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Pipeline 2 Warm Dim Ceiling Light with Remote Power

By PureEdge Lighting



### Description

Pipeline 2 Warm Dim Ceiling with Remote End Feed Power and Round Canopy is a linear LED fixture that offers a clean, uninterrupted beam of light through a diffused 280 degree white lens. Pipeline 2 is available in various increments from 12 to 240 inches, includes 5 LED watts per foot, and Warm Dim 2700K to 2000K (27D) or 3000K to 2000K (30D) color temperature. Unlike standard LEDs, Warm Dim LEDs are designed to shift to a warmer color temperature as they are dimmed, replicating the effects of incandescent and halogen light sources. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply/ dimmable ELV) which fits inside junction box, or from a remote Universal (UNI) power supply (dimmable ELV/TRIAC/0-10V). Required power supply and dimmer control sold separately. Note: Includes one 4.6 inch round canopy and mounting clips for every 18 inch length.

### Specifications




COLOR . . . . . N/A  
BODY FINISH . . . . . Satin Nickel  
WATTAGE . . . . . 5W  
DIMMER . . . . . Low Voltage Electronic  
DIMENSIONS . . . . . 12"L x 1.25"W x 1.25"H  
INTEGRATED LED MODULE . . . . . 1 x LED/5W/24V LED

### Technical Information

LAMP LIFE . . . . . 50000 hours  
COLOR RENDERING . . . . . 95 CRI  
LAMP COLOR . . . . . 2700K Warm Dim  
LUMENS/WATT . . . . . 82.80  
LUMINOUS FLUX . . . . . 414 lumens



Shown in satin nickel



CLICK TO VIEW PRODUCT

Notes: