

Lightology

lightology.com
866-954-4489
04-25-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG797357**
 Approved On: _____ Approved By: _____

Pipeline 2 Warm Dim Ceiling Light with Remote Power

By PureEdge Lighting



Description

Pipeline 2 Warm Dim Ceiling Light with Remote End Feed Power and Round Canopy is a linear LED fixture that offers a clean, uninterrupted beam of light through a diffused 280 degree white lens. Pipeline 2 is available in various increments from 12 to 240 inches, includes 5 LED watts per foot, and Warm Dim 2700K to 2000K (27D) or 3000K to 2000K (30D) color temperature. Unlike standard LEDs, Warm Dim LEDs are designed to shift to a warmer color temperature as they are dimmed, replicating the effects of incandescent and halogen light sources. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply/ dimmable ELV) which fits inside junction box, or from a remote Universal (UNI) power supply (dimmable ELV/TRIAC/0-10V). Required power supply and dimmer control sold separately. Note: Includes one 4.6 inch round canopy and mounting clips for every 18 inch length.

Specifications


COLOR	N/A
BODY FINISH	Satin Nickel
WATTAGE	5W
DIMMER	Low Voltage Electronic
DIMENSIONS	12"L x 1.25"W x 1.25"H
INTEGRATED LED MODULE	1 x LED/5W/24V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	2700K Warm Dim
LUMENS/WATT	82.80
LUMINOUS FLUX	414 lumens



Shown in satin nickel



CLICK TO VIEW PRODUCT

Notes: