

Lightology

lightology.com
866-954-4489
08-04-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG797367**
Approved On: _____ Approved By: _____

Pipeline 2 Ceiling Light with Remote Power

By PureEdge Lighting



Description

Pipeline 2 Ceiling with Remote End Feed Power and Round Canopy is a linear LED fixture that offers a clean, uninterrupted beam of light through a diffused 280 degree white lens. Pipeline 2 is available in various increments from 12 to 240 inches, two wattage options, multiple finish options, and a spectrum of color temperature options. ETL listed. Title 24 compliant when used with a Universal (UNI) power supply. Fixture includes a 5 year warranty. Product is built to order. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply/dimmable ELV) which fits inside junction box, or from a remote Universal (UNI) power supply (dimmable ELV/TRIAC/0-10V). Required power supply and dimmer control sold separately. Note: Includes one 4.6 inch round canopy and mounting clips for every 18 inch length.

Specifications



COLOR N/A
BODY FINISH Satin Nickel
WATTAGE 5W
DIMMER Low Voltage Electronic
DIMENSIONS 12"L x 1.25"W x 1.25"H
INTEGRATED LED MODULE 1 x LED/5W/24V LED

Technical Information

LAMP LIFE 50000 hours
COLOR RENDERING 95 CRI
LAMP COLOR 2700K
LUMENS/WATT 65.80
LUMINOUS FLUX 329 lumens



Shown in satin nickel



CLICK TO VIEW PRODUCT

Notes: