

Lightology

lightology.com
866-954-4489
08-17-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG797625**
Approved On: _____ Approved By: _____

Pipeline 2 Power Warm Dim Downlight Suspension Center Feed

By PureEdge Lighting



Description

Pipeline 2 Warm Dim Downlight Suspension with Center Power Feed is a linear LED fixture with a clean and contemporary style. Pipeline 2 is available in various increments from 36 to 120 inches and features a diffused white lens, 4.4 LED watts per foot, Warm Dim 2700K to 2000K (27D) or 3000K to 2000K (30D) color temperature. Chrome finish available up to 84 inch length. Includes a linear canopy with 120V/24VDC output Universal (UNI) LED power supply (dimmable ELV/TRIAC/0-10V) and 12 foot coaxial aircraft cables. Additional aircraft cables included for support when fixture exceeds 72 inches. Canopy size dependent on length of fixture. Note: Product is built to order.

Specifications


COLOR N/A
BODY FINISH Satin Nickel
WATTAGE 15W
DIMMER Low Voltage Electronic
DIMENSIONS 36"L x 1.25"W x 1.25"H
INTEGRATED LED MODULE 3 x LED/5W/120V LED

Technical Information

LAMP LIFE 50000 hours
COLOR RENDERING 95 CRI
LAMP COLOR 2700K Warm Dim
LUMENS/WATT 248.40
LUMINOUS FLUX 1242 lumens



Shown in satin nickel



CLICK TO VIEW PRODUCT

Notes: