

Lightology

lightology.com
866-954-4489
06-01-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG799314**
 Approved On: _____ Approved By: _____

Pix Sticks Tie Stix Wood Suspension with Remote Power

By PureEdge Lighting



Description

The Pix Sticks Tie Stix Wood Suspension with Remote Power is the essence of modernity with alluring sleek metal finishes that demand attention. Remote power allows for easier replacement in hard-to-reach spaces such as atriums. Features linear channels that intersect at alternate heights casting downlight illumination through diffused white lenses. Includes 5 or 7 watts per foot per channel in a variety of color temperature options including Warm Dim. Channel finishes in Wood Cherry, Wood Walnut, Wood White Oak, Wood Espresso and Wood Maple. Hardware finish available in Satin Nickel, Satin Black, Chrome, White or Antique Bronze. Satin Nickel and White finishes supplied with matching canopy and hardware. Satin Black, Antique Bronze and Chrome finishes supplied with a Black canopy. Offered in three, five or seven stick channel options from 39-96 inches in length. Supplied with a metal canopy (12 inch for 3 and 5-stick and 16 inch for 7-stick), and 12 feet of suspension cable. Note: Requires a remote power supply: PS-60L-ELV-24VDC (50 Watt Non-IC 24 Volt DC Power Supply) which fits inside junction box, or from a remote Universal (UNI) power supply. Required remote power supply and dimmer control sold separately.

Specifications


COLOR Wood White Oak
 BODY FINISH Satin Nickel
 WATTAGE 100W
 DIMMER Low Voltage Electronic
 DIMENSIONS 48"L x 1.24"W x 1.24"H
 INTEGRATED LED MODULE 20 x LED/5W/24V LED

Technical Information

LAMP LIFE 50000 hours
 COLOR RENDERING 92 CRI
 LAMP COLOR 2700K
 LUMENS/WATT 1,080.00
 LUMINOUS FLUX 5400 lumens



Shown in satin nickel / wood white oak



PIX STICKS TIE STIX SUSPENSION WITH REMOTE POWER - ACTUAL SIZES		
Ordering code (Minimum Size)	Actual channel channel length (inches)	Actual channel channel length (feet)
39	39.0	3.25
48	48.0	4.0
60	60.0	5.0
72	72.0	6.0
84	84.0	7.0
96	96.0	8.0



CLICK TO VIEW PRODUCT

Notes: