

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG821551	
Approved On:	Approved By:

Cirrus Ceiling D1 Warm Dim HE Downlight w/ Remote Power By PureEdge Lighting





Description

Cirrus Ceiling Channel D1 Lens Warm Dim High Efficiency (HE) Downlight with Remote Power is a linear LED fixture that offers direct light in a clean, contemporary style. Cirrus is available in various increments from 12 to 240 inches, features a 60 degree beam spread clear frosted or 100 degree beam spread diffused white lens, 5 LED watts per foot, and Warm Dim 2700K-1900K (27D) or 3000K-2200K (30D) color temperature. ETL listed. Title 24 compliant when used with Univeral (UNI) power supply. Fixture includes a 5 year warranty. Product is built to order. Note: Pre-wired for use with remote power supplies: PS-60L-ELV-24VDC (60 Watt Non-IC 24 Volt DC Power Supply) which fits inside junction box, or from a remote Universal (UNI) power supply. Required remote power supply, dimmer control, and optional mounting accessories, sold separately. Note: Includes a 4.6 inch square canopy. Mounting clips (C-MCL) are included for use every 24 inches.

Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER
DIMENSIONS
INTEGRATED LED MODULE

Technical Information

LAMP LIFE															50	000	00	ho	urs	
COLOR RENDERIN	٩G																. 9	95 (CRI	
LAMP COLOR													270	00	Κ	Wa	irn	n D	im	
LUMENS/WATT .																		58	.20	
LUMINOUS FLUX																291	lu	me	ns	



Shown in satin nickel / white lens





CLICK TO VIEW PRODUCT

Notes:	