

lightology.com 866-954-4489 08-30-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG827071	
Approved On:	Approved By:

Cirrus Ceiling S1 Lens Warm Dim Downlight w/ Remote Power By PureEdge Lighting





Description


Cirrus Ceiling Channel SI Lens Warm Dim Downlight with Remote Power is a linear LED fixture that offers direct light in a clean, contemporary style. Cirrus is available in various increments from 12 to 240 inches, features a square lens with 105 degree beam, 5 LED watts per foot, and Warm Dim 2700K-2000K (27D) or 3000K-2000K (30D) color temperature. Unlike standard LEDs, Warm Dim LEDs are designed to shift to a warmer color temperature as they are dimmed, replicating the effects of incandescent and halogen light sources. Includes a 4.6 inch square canopy that mounts on a standard junction box. May be ordered with a Slim Profile Channel Junction Box (C-1RE-JBOX), sold separately. Mounting clips (CC-MCL) are included for use every 18 inches. Lengths over 96 inches ship as two segments. Maximum shipping length for Chrome finish is 84 inches. Product is built to order. Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (50 Watt Non-IC 24 Volt DC Power Supply) which fits inside junction box, or from a remote Universal (UNI) power supply feeding 24VDC up to 100 watts at a maximum of 40 feet away. Required power supply, dimmer control, and optional mounting accessories, sold separately. Note: Limited quantities available in Bronze finish.

Specifications

BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE
Technical Information
COLOR RENDERING
LAMP COLOR



Shown in satin nickel





CLICK TO VIEW PRODUCT

Notes:	
Notes:	