

# Lightology

lightology.com  
866-954-4489  
05-20-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **NOR868825**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## NL Series 4IN 120V Non-IC Airtight Remodel Housing By Nora Lighting



### Description

The NL Series 4 Inch Non-IC Airtight Remodel Housing is constructed of one piece white baked enamel steel and allows for adjustable ceiling thickness from 3/8 to 1.38 inch. Rated for use with a 120 volt MR16 GU10 lamp (housing includes MR16 GU10 with 40 degree beam spread). Non-IC housings require a minimum clearance of 3 inches from thermal insulation. UL listed. Suitable for damp locations (or wet locations with designated trims). Meets or exceeds ASTM-283 Air-Tight requirements. Dimmable with a standard incandescent dimmer, sold separately. A complete fixture includes a housing and trim, sold separately.

### Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	50W
DIMMER	Standard 120V
DIMENSIONS	11.25"W x 5.63"H x 4.25"D
BULB INCLUDED	1 x MR16/GU10/50W/120V Halogen

### Technical Information

APERTURE SIZE	4.000"
HOUSING HEIGHT	6"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim



Shown in white



CLICK TO VIEW PRODUCT

Notes: