

# Lightology

lightology.com  
866-954-4489  
04-25-26

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG872164**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## 3X96W 24 Volt Universal DC LED Power Supply By PureEdge Lighting




### Description


The PSB-3X96W-UNV-24VDC LED Class 2 power supply accepts input voltage of 120-277VAC and outputs 24VDC power up to 3X96 watts. The solid state constant voltage Uni-power supply is compatible with most commercially available dimmers: Triac (forward phase) used for dimming of incandescent and low voltage magnetic transformers; ELV (reverse phase) - used for dimming electronic low voltage transformers; or 0-10V dims the low voltage side of a 0-10V power supply commonly used in large scale lighting or commercial applications. Auto-reset, short circuit, and overload and thermal protection. UL & ETL recognized/listed, meets UL 8750, 1310 requirements. Title 24 compliant. Available in a remote and T-Bar mount option.



Shown in white



Top View



Side View

### Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	288W
DIMMER	Low Voltage Electronic
DIMENSIONS	14"W x 2.82"H x 10"D
BULB NOT INCLUDED	N/A



CLICK TO VIEW PRODUCT

Notes: