

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: <b>NOR882730</b>	
Approved On:	Approved By:

## NL Series 4IN 120V IC Airtight New Construction Housing By Nora Lighting







## Description


The NL Series 4 Inch IC Airtight New Construction Housing is constructed of one piece white baked enamel steel and allows for adjustable ceiling thickness from 5/8 to 1.38 inch. Rated for use with a 120 volt MR16 GU10 lamp (housing includes MR16 GU10 with 40 degree beam spread). Non-IC housings require a minimum clearance of 3 inches from thermal insulation. UL listed. Suitable for damp locations (or wet locations with designated trims). Meets or exceeds ASTM-283 Air-Tight requirements. Dimmable with a standard incandescent dimmer, sold separately. Note: A complete fixture includes a housing and trim, sold separately.

## Specifications

REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER
DIMENSIONS
BULB INCLUDED
OTHER BULB OPTIONS
Technical Information
APERTURE SIZE
HOUSING HEIGHT
HOUSING TYPE



Shown in white



Cut-out: 4-3/8" ID: 4" Housing Length: 12-5/8" Housing Width: 8" Housing Height: 8"



CLICK TO VIEW PRODUCT

Notes: