

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG89129	
Approved On:	Approved By:

Cirrus Ceiling D1 Lens Downlight w/ Remote Power By PureEdge Lighting





Description

Cirrus Ceiling Channel D1 Lens Static White Downlight with Remote 24VDC Power is a linear LED fixture that offers direct light in a clean, contemporary style. Cirrus is available in various increments from 12 to 480 inches, features a 60 degree beam spread clear frosted or 100 degree beam spread diffused white lens, optional black or white louver, four wattage options, and a spectrum of color temperature options. Includes a 4 inch square canopy and mounting clips (C-MCL) for use every 24 inches. Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (50 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Note: Required power supply, dimmer control, and optional accessories sold separately.

Specifications


COLOR	าร
BODY FINISH	el
WATTAGE	Ν
DIMMER Low Voltage Electron	ic
DIMENSIONS	Н
INTEGRATED LED MODULE	\Box

Technical Information

LAMP LIFE														ļ	50	00	0h	our	S
BEAM ANGLE																		100	0
COLOR REND	ERIN	G.															95	CR	15
LAMP COLOR																	27	100	<
LUMENS/WA	т.																. 4	7.00	С
I UMINOUS FI	UX														2	35 '	lum	nen	s



Shown in satin nickel / white lens





CLICK TO VIEW PRODUCT

Notes:	