

Lightology

lightology.com
866-954-4489
04-04-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG89129**
 Approved On: _____ Approved By: _____

Cirrus Ceiling D1 Lens Downlight w/ Remote Power

By PureEdge Lighting



Description

Cirrus Ceiling Channel D1 Lens Static White Downlight with Remote 24VDC Power is a linear LED fixture that offers direct light in a clean, contemporary style. Cirrus is available in various increments from 12 to 480 inches, features a 60 degree beam spread clear frosted or 100 degree beam spread diffused white lens, optional black or white louver, four wattage options, and a spectrum of color temperature options. Includes a 4 inch square canopy and mounting clips (C-MCL) for use every 24 inches. Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (50 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Note: Required power supply, dimmer control, and optional accessories sold separately.

Specifications


COLOR White Lens
 BODY FINISH Satin Nickel
 WATTAGE 5W
 DIMMER Low Voltage Electronic
 DIMENSIONS 12"L x 0.9"W x 0.9"H
 INTEGRATED LED MODULE 1 x LED/5W/24V LED

Technical Information

LAMP LIFE 50000 hours
 BEAM ANGLE 100°
 COLOR RENDERING 95 CRI
 LAMP COLOR 2700K
 LUMENS/WATT 47.00
 LUMINOUS FLUX 235 lumens



Shown in satin nickel / white lens



CLICK TO VIEW PRODUCT

Notes: