



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Cirrus Ceiling Channel D1 Lens Static White Downlight with Remote 24VDC Power is a linear LED fixture that offers direct light in a clean, contemporary style. Cirrus is available in various increments from 12 to 480 inches, features a 60 degree beam spread clear frosted or 100 degree beam spread diffused white lens, optional black or white louver, four wattage options, and a spectrum of color temperature options. Includes a 4 inch square canopy and mounting clips (C-MCL) for use every 24 inches. Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (50 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Note: Required power supply, dimmer control, and optional accessories sold separately.




Shown in: Satin Nickel / White Lens

SHADE COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	5W
DIMMER	Low Voltage Electronic
DIMENSIONS	12"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE	
LAMP	1 x LED/5W/24V LED

Technical Information

LUMINOUS FLUX	235 lumens
LUMENS/WATT	47.00
LAMP COLOR	2700K
COLOR RENDERING	95 CRI
BEAM ANGLE	100°

SPEC # EDG89129



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE
