Lightology

lightology.com
866-954-4489
11-05-26

Project:

Company:

Location: Fixture Type:

SPEC #: **ELE892108**

Approved On: Approved By:

Entra 3IN RD Adjustable IC New Construction Housing


By Visual Comfort Architectural


Description

Entra is easy to configure with a complete feature set that offers flexibility without an overwhelming list of options. The 3 Inch Round Adjustable Downlight and Wall Wash IC New Construction Housing is offered with low (12 watt) output, four color temperature options including Warm Dim (3000K - 1800K), and 20-40-65 degree interchangeable optics with hot aiming (30 degree tilt, 359 degree rotation). LED module ships with 40 degree optic installed. Adjust to 30 degree tilt for wall wash applications. 4 inch cut out. Dimmable with a Triac, electronic low voltage (ELV) or 0-10V dimmer, sold separately. ETL listed. Energy Star. Suitable for damp locations. Can be used to comply with CEC 2016 Title 24 Part 6. A complete fixture requires a housing and trim (with or without flange), sold separately



Shown in black





Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	11W
DIMMER	Low Voltage Electronic
DIMENSIONS	12.2"W x 3.5"H x 7.3"D
INTEGRATED LED MODULE	1 x LED/11W/120-277V LED

Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Round
HOUSING TYPE	New construction IC Airtight
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	65°
COLOR RENDERING	90 CRI
LAMP COLOR	2700K
LUMENS/WATT	77.82
LUMINOUS FLUX	856 lumens

CLICK TO VIEW PRODUCT

Notes: