

Lightology

lightology.com
866-954-4489
07-04-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **WAC896012**
Approved On: _____ Approved By: _____

Ocularc 3.5IN RD Non-IC Remodel Housing By WAC Lighting



Description


The Oculux Architectural 3.5 Inch Round Non-IC Remodel Housing features a single spot light source with 0-30 degree vertical adjustment and 365 degree horizontal adjustment. Non-IC remodel housing with integral light engine and driver concealed within the fixture. Non-IC designation requires a 3 inch minimum clearance away from insulation. Accepts one honeycomb louver or optical accessory, sold separately. ETL listed. Title 24 compliant. Suitable for wet locations. Dimmable with an electronic low voltage (ELV), 0-10V or TRIAC dimming (see attached manufacturer reference for dimmer compatibility). A complete fixture includes a housing and trim, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	11W
DIMMER	0-10V
DIMENSIONS	4.5"W x 3.75"H x 11"D
INTEGRATED LED MODULE	1 x LED/11W/120V LED

Technical Information

APERTURE SIZE	3.500"
APERTURE SHAPE	Round
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim
LAMP LIFE	50000 hours
COLOR RENDERING	90 CRI
LAMP COLOR	2700K



Shown in black



CLICK TO VIEW PRODUCT

Notes: