

# Lightology

lightology.com  
866-954-4489  
07-17-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG90370**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Cirrus Ceiling S1 Lens Downlight w/ Remote Power

By PureEdge Lighting



### Description

Cirrus Ceiling Channel S1 Lens Downlight with Remote Power is a linear LED fixture that offers direct light in a clean, contemporary style. Cirrus is available in various increments from 12 to 480 inches, features a square lens with 105 degree beam, three wattage options, and a spectrum of color temperature options. Maximum shipping length for Chrome is 84 inches. Includes a 4.6 inch square canopy. May be ordered with a Slim Profile Channel Junction Box (C-1RE-JBOX), sold separately. Mounting clips (CC-MCL) are included for use every 18 inches. Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (50 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Required power supply, dimmer control, and optional accessories sold separately. Note: Limited quantities available in Bronze finish.

### Specifications


COLOR . . . . . N/A  
BODY FINISH . . . . . Satin Aluminum  
WATTAGE . . . . . 2W  
DIMMER . . . . . Dimmable  
DIMENSIONS . . . . . 12"L x 0.9"W x 0.9"H  
INTEGRATED LED MODULE . . . . . 1 x LED/2W/24V LED

### Technical Information

LAMP LIFE . . . . . 50000 hours  
BEAM ANGLE . . . . . 105°  
COLOR RENDERING . . . . . 95 CRI  
LAMP COLOR . . . . . 2700K



Shown in satin aluminum



CLICK TO VIEW PRODUCT

Notes: