

Lightology

lightology.com
866-954-4489
07-10-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG906468**
 Approved On: _____ Approved By: _____

2X60W 24 Volt Universal DC LED Power Supply By PureEdge Lighting




Description


The PSB-2X60W-UNV-24VDC LED Class 2 power supply accepts input voltage of 120-277VAC and outputs 24VDC power up to 2X60 watts. The solid state constant voltage Uni-power supply is compatible with most commercially available dimmers: Triac (forward phase) - used for dimming of incandescent and low voltage magnetic transformers; ELV (reverse phase) - used for dimming electronic low voltage transformers; or 0-10V dims the low voltage side of a 0-10V power supply commonly used in large scale lighting or commercial applications. Auto-reset, short circuit, and overload and thermal protection. UL & ETL recognized/listed, meets UL 8750, 1310 requirements. Title 24 compliant. Available in a remote and T-bar mount option.



Shown in white



Top View



Side View

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	60W
DIMMER	Low Voltage Electronic
DIMENSIONS	12.15"W x 2.18"H x 6.48"D
BULB NOT INCLUDED	N/A



CLICK TO VIEW PRODUCT

Notes: