

Lightology

lightology.com
866-954-4489
03-30-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **WAC925008**

Approved On: _____ Approved By: _____

Ion 2 inch Square 3000K Recessed Trim/New Construction Housing By WAC Lighting



Description

The Ion 2 Inch Square Downlight Trim with IC Airtight New Construction Housing is designed for new construction applications only. IC designation allows for insulation to be in direct contact with housing. White finish with frosted TIR lens. Includes dimmable LED module and driver featuring switch selectable color temperature options including 2700K, 3000K, 3500K, 4000K, and 5000K. 35 degree beam angle. ETL listed. Energy Star. Rated for wet locations. Title 24 compliant. Dimmable with an electronic low voltage (ELV) or Triac dimmer, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR	Frosted
BODY FINISH	White
WATTAGE	9W
DIMMER	Low Voltage Electronic
DIMENSIONS	3.5"W x 3.88"H
INTEGRATED LED MODULE	1 x LED/9W/120V LED
COUNTRY OF ORIGIN	China

Technical Information

APERTURE SIZE	2.000"
APERTURE SHAPE	Square
HOUSING HEIGHT	4"
HOUSING TYPE	New construction IC Airtight
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	35°
COLOR RENDERING	90 CRI
LAMP COLOR	3000K
LUMENS/WATT	81.67
LUMINOUS FLUX	735 lumens



Shown in white / frosted



CLICK TO VIEW PRODUCT

Notes: