



BRAND Visual Comfort Architectural

DESCRIPTION

The 2 Inch Round Flanged Adjustable Downlight Chicago Plenum Housing is constructed of heavy gauge cold rolled steel with a durable Black powder coat finish. This specification grade housing features an integral 12 watt (average 930 lumens) or 17 watt (average 1250 lumens) LED module in three color temperature options with 20, 30, 40 or 60 degree beam angle, or Warm Dim (3000K to 1800K) in low output 12 watt (average 850 lumens) and 20, 30, 40 or 60 degree beam angle. 2.75 inch ceiling cutout, suitable for ceilings up to 2 inch thick. ETL listed. Suitable for damp locations. Title 24 compliant. 5 year warranty. 120-277V Universal driver with standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming down to 1%, sold separately. A complete fixture requires a housing and trim, sold separately. Note: Warm Dim option available in low output only (12 Watt).




Shown in: Black

TRIM COLOR	N/A
BODY FINISH	Black
WATTAGE	12W
DIMMER	Low Voltage Electronic
DIMENSIONS	12"L x 10"W x 5.25"H
INTEGRATED LED MODULE	
LAMP	1 x LED/120-277V LED

Technical Information

LUMINOUS FLUX	939 lumens
LUMENS/WATT	78.25
LAMP COLOR	2700K
COLOR RENDERING	90 CRI
BEAM ANGLE	20°
LAMP LIFE	50000 hours
CEILING TYPE	Drywall with Trim
HOUSING TYPE	Chicago plenum approved
HOUSING HEIGHT	6"
SPEC #	ELE929462



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE