

Lightology

lightology.com
866-954-4489
07-05-25

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **ELE931050**

Approved On: _____ Approved By: _____

Multiples 1 X 1 Open Flangeless IC Airtight Housing

By Visual Comfort Architectural



Description


Multiples 1 X 1 Open Flangeless IC Airtight Housing for Open Light Modules features a patented LED spot dome module with a remarkable tool-free adjustment and locking mechanism. Constant current driver. Dimmable with an electronic low voltage (down to 1 percent) or 0-10V dimmer (down to 5 percent), sold separately. 5 inch ceiling opening. ETL listed for damp location. Title 24 Compliant. 5 year warranty. Requires an Element Lighting Multiples Open Light Module, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	12W
DIMMER	Low Voltage Electronic
DIMENSIONS	10"L x 9"W x 6"H
INTEGRATED LED MODULE	1 x LED/12W/120-277V LED

Technical Information

APERTURE SIZE	5.000"
APERTURE SHAPE	Square
HOUSING HEIGHT	5"
HOUSING TYPE	New construction IC Airtight
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Downlight
COLOR RENDERING	80 CRI
LUMENS/WATT	104.67
LUMINOUS FLUX	1256 lumens



Shown in white



CLICK TO VIEW PRODUCT

Notes: