

Lightology

lightology.com
866-954-4489
04-27-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **ELE931114**
 Approved On: _____ Approved By: _____

Multiples 1 X 3 Open Flanged Non IC Airtight Housing By Visual Comfort Architectural



Description


Multiples 1 X 3 Open Flanged Non IC Airtight Housing for Open Light Modules features a patented LED spot dome module with a remarkable tool-free adjustment and locking mechanism. Housing available in low and high output options (see light module for more information). Constant current driver. Dimmable with an electronic low voltage (down to 1 percent) or 0-10V dimmer (down to 5 percent), sold separately. 5 inch ceiling opening. ETL listed for damp location. Title 24 Compliant. 5 year warranty. Requires three Element Lighting Multiples Open Light Modules, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	36W
DIMMER	Low Voltage Electronic
DIMENSIONS	19.9"L x 7.5"W x 5.8"H
INTEGRATED LED MODULE	3 x LED/12W/120-277V LED

Technical Information

APERTURE SIZE	5.000"
APERTURE SHAPE	Rectangular
HOUSING HEIGHT	6"
HOUSING TYPE	New construction NON IC Airtight
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LUMENS/WATT	314.00
LUMINOUS FLUX	3768 lumens



Shown in white



CLICK TO VIEW PRODUCT

Notes: