

Lightology

lightology.com
866-954-4489
05-24-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **ELE931170**
 Approved On: _____ Approved By: _____


Multiples 1 X 4 Open Flangeless IC Airtight Housing

By Visual Comfort Architectural




Description

Multiples 1 X 4 Open Flangeless IC Airtight Housing for Open Light Modules features a patented LED spot dome module with a remarkable tool-free adjustment and locking mechanism. Constant current driver. Dimmable with an electronic low voltage (down to 1 percent) or 0-10V dimmer (down to 5 percent), sold separately. 5 inch ceiling opening. ETL listed for damp location. Title 24 Compliant. 5 year warranty. Requires four Element Lighting Multiples Open Light Modules, sold separately.



Shown in white



Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	48W
DIMMER	Low Voltage Electronic
DIMENSIONS	24.9"L x 8.7"W x 5.8"H
INTEGRATED LED MODULE	4 x LED/12W/120V LED

Technical Information

APERTURE SIZE	5.000"
APERTURE SHAPE	Rectangular
HOUSING HEIGHT	6"
HOUSING TYPE	New construction IC Airtight
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LUMENS/WATT	418.67
LUMINOUS FLUX	5024 lumens



CLICK TO VIEW PRODUCT

Notes: