

Lightology

lightology.com
866-954-4489
04-28-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **ELE934725**

Approved On: _____ Approved By: _____

1X3 Trimmed Flanged IC Airtight Housing By Visual Comfort Architectural



Description


1X3 Trimmed Flanged 3-Light Low Output (3 x 12 watt) IC Airtight Housing is constructed of heavy gauge cold rolled steel with durable Black or White powder coat finish. Features a unique patented LED spot dome module enabling tool-free adjustment and locking while maintaining center beam through the aperture. Low profile design for use in standard 2X6 construction. Accommodates up to 2 inch ceiling thickness. Includes integrated junction box approved for branch circuit through wiring. Housing includes individual driver for each module (ie: 3 drivers in a 1x3). 5 inch x 5 inch ceiling cut-out per module. ETL listed. Suitable for damp locations. 5 year warranty. Dimming Options: Electronic low voltage (ELV) down to

Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	36W
DIMMER	Low Voltage Electronic
DIMENSIONS	19.9"L x 8.7"W x 5.8"H
INTEGRATED LED MODULE	3 x LED/12W/120-277V LED

Technical Information

APERTURE SIZE	2.800"
APERTURE SHAPE	Rectangular
HOUSING HEIGHT	6"
HOUSING TYPE	New construction IC Airtight
CEILING TYPE	Drywall with Trim
LUMENS/WATT	312.00
LUMINOUS FLUX	3744 lumens



Shown in black



CLICK TO VIEW PRODUCT

Notes: