

Lightology

lightology.com
866-954-4489
12-29-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **ELE940034**
Approved On: _____ Approved By: _____

Element 3IN RD Flanged Adj Shallow New Construction Housing

By Visual Comfort Architectural



Description

3 Inch Round 90CRI Flanged Adjustable Downlight IC Airtight or Chicago Plenum New Construction Housing for round flanged trims. Lockable, hot aiming with 0-40 degree tilt and 361 degree rotation. This small aperture LED downlight is fully adjustable and the design allows the LED to be positioned closer to the aperture for maximum light output and efficiency, or higher to minimize glare on the trim. Includes a 12 or 17 watt LED module with 10, 18, 25, 40 or 60 degree beam angle options. 3 7/8 inch ceiling opening. Suitable for damp locations. Suitable for wet locations with shower trim option. Includes a 120-277V Universal driver dimmable with standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming. Note: A complete fixture requires a housing and trim, sold separately. Note: Warm Dim option is not available with 10 degree beam angle.

Specifications


REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Black Powder Coat
WATTAGE 17W
DIMMER Low Voltage Electronic
DIMENSIONS 12.5"L x 9.5"W x 3"H
INTEGRATED LED MODULE 1 x LED/17W/120-277V LED

Technical Information

APERTURE SHAPE Round
HOUSING HEIGHT 3"
HOUSING TYPE Chicago plenum approved
CEILING TYPE Drywall with Trim
FUNCTION Adjustable Accent
LAMP LIFE 50000 hours
BEAM ANGLE 25°
COLOR RENDERING 90 CRI
LAMP COLOR 3000K
LUMENS/WATT 90.00
LUMINOUS FLUX 1530 lumens



Shown in black powder coat



IC AIRTIGHT / CHICAGO PLENUM



CLICK TO VIEW PRODUCT

Notes: