

SPEC #









ELE946478

BRAND

Visual Comfort Architectural

DESCRIPTION

3 Inch Square 90CRI Flangeless Fixed Downlight Non-IC Airtight, IC Airtight, or Chicago Plenum New Construction Housing for square flangeless trims. Small aperture LED downlight with architectural appearance. Includes a 12 or 17 watt LED module in three color temperature options and Warm Dim LED (3000K-1800K). Offered with a 10, 18, 25, 40 or 60 degree beam angle. 3 7/8 inch ceiling opening. Suitable for damp locations. Suitable for wet locations with shower trim option. Includes a 120-277V Universal driver dimmable with standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming. Note: A complete fixture requires a housing and trim, sold separately. Note: Warm Dim option is not available with 10 degree beam angle.



Shown in: Black


TRIM COLOR N/A **BODY FINISH** Black WATTAGE 12\\\ DIMMER Low Voltage Electronic DIMENSIONS 12.5"L x 9.5"W x 4"H INTEGRATED LED MODULE

LAMP 1 x LED/12W/120-277V LED

Technical Information

LUMINOUS FLUX 1065 lumens LUMENS/WATT 88.75 LAMP COLOR 2700K COLOR RENDERING 90 CRI BEAM ANGLE 10° LAMP LIFE 50000 hours FUNCTION Downlight CEILING TYPE Drywall Trimless/Flush HOUSING TYPE New construction IC Airtight

SPEC # ELE946478



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE