

Lightology

lightology.com
866-954-4489
04-25-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG950334**
 Approved On: _____ Approved By: _____

Pipeline 2 Vanity Wall End Feed w/ Power By PureEdge Lighting



Description

The Pipeline 2 Vanity Wall Light with End Feed features a tubular diffuser with a 147 degree beam angle and 280 degrees of diffused light. Available in a variety of finishes, a spectrum of color temperatures options including Warm Dim, 5 LED watts per foot (lengths from 10 to 120 inches), and 7 LED watts per foot (from 10 to 72 inches). Includes a 120V-24VDC Universal power supply (dimmable ELV/TRIAC/0-10V) which fits inside a standard junction box and a 4.6 inch round end feed canopy. ETL listed. ADA compliant. Suitable for indoor damp locations. 5 year pro-rated warranty. NOTE: 7 WATT MAX LENGTH = 72 INCH. CHROME FINISH AVAILABLE UP TO 84 INCH ON 5 WATT AND 72 INCH ON 7 WATT.

Specifications


COLOR White
 BODY FINISH Chrome
 WATTAGE 10W
 DIMMER Low Voltage Electronic
 DIMENSIONS 20"L x 4.6"W x 1.58"D
 INTEGRATED LED MODULE 2 x LED/5W/120V LED

Technical Information

LAMP LIFE 60000 hours
 COLOR RENDERING 95 CRI
 LAMP COLOR 2700K
 LUMENS/WATT 109.60
 LUMINOUS FLUX 548 lumens



Shown in chrome / white



Ordering Code	Lens Length	STATIC WHITE (22K, 24K, 27K, 30K, 35K, 40K & 57K)				Total Lumens 3000K (lm)	Total Lumens 5000K (lm)
		Overall Length Dimension W' E18-E182	Overall Length Dimension W' E4R	Overall Length Dimension W' E4R2	Total Wattage (W)		
12	12	15	17	2	557.0	77.5	911
20	19.2	20.2	22.2	24.2	8	862	1043
24	24	25	27	29	10	1100	1310
30	31.2	32.2	34.2	36.2	13	1434	1744
36	36	37	39	41	15	1654	2005
48	48	49	51	53	20	2206	2670
60	60	61	63	65	25	2737	3325
72	72	73	75	77	30	3300	4010
84*	79.2	80.2	82.2	84.2	33	3639	4373
84*	84	85	87	89	35	3860	4673
96	96.4	97.4	99.4	101.4	38	4170	5010
96	96.4	96.4	101.4	103.4	41	4322	
108	108	109	111	113	45	4963	
120	120	121	123	125	50	5514	

*72" Max Length *Maximum length for Chrome is 84"



CLICK TO VIEW PRODUCT

Notes: _____