

lightology.com 866-954-4489 12-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: <b>EDG950334</b>	
Approved On:	Approved By:

## Pipeline 2 Vanity Wall End Feed w/ Power By PureEdge Lighting







## Description

The Pipeline 2 Vanity Wall Light with End Feed features a tubular diffuser with a 147 degree beam angle and 280 degrees of diffused light. Available in a variety of finishes, a spectrum of color temperatures options including Warm Dim, 5 LED watts per foot (lengths from 10 to 120 inches), and 7 LED watts per foot (from 10 to 72 inches). Includes a 120V-24VDC Universal power supply (dimmable ELV/TRIAC/0-10V) which fits inside a standard junction box and a 4.6 inch round end feed canopy. ETL listed. ADA compliant. Suitable for indoor damp locations. 5 year pro-rated warranty. NOTE: 7 WATT MAX LENGTH = 72 INCH. CHROME FINISH AVAILABLE UP TO 84 INCH ON 5 WATT AND 72 INCH ON 7 WATT.

## Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE 2 x LED/5W/120V LED

## Technical Information

LAMP LIFE	 60000 hours
COLOR RENDERING	 95 CRI
LAMP COLOR	 2700K
LUMENS/WATT	 109.60
LUMINOUS FLUX	 . 548 lumens



Shown in chrome / white



STATIC WHITE (22K, 24K, 27K, 30K, 35K, 40K & 57K)								
Ordering Code Example	Lens Length	Overall Length Dimension 'A' E1R+E1R2	Overall Length Dimension 'B' E4R	Overall Length Dimension 'B' E4R2	Total Wattage (5W)	Total Lumens 3000K (SW)	Total Wattage (7W)	Total Lumens 3000K (7W)
12	12	13	15	17	5	557.0	7.5	911
20	19.2	20.2	22.2	24.2	8	892	12.0	1443
24	24	25	27	29	10	1103	15.0	1803
32	31.2	32.2	34.2	36.2	13	1434	19.5	2344
36	36	37	39	41	15	1654	22.5	2705
48	48	49	51	53	20	2206	30.0	3607
60	60	61	63	65	25	2757	37.5	4509
72	72	73	75	77	30	3309	45.0	5411
80	79.2	80.2	82.2	84.2	33	3639	49.5	5952
84"	84	85	87	89	35	3860	52.5	6313
87	86.4	87.4	89.4	91.4	36	3970		
99	98.4	99.4	101.4	103.4	41	4522		
108	108	109	111	113	45	4963		
120	120	121	123	125	50	5514		



**CLICK TO VIEW PRODUCT** 

Notes:	