

Lightology

lightology.com
866-954-4489
08-04-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **ELE963716**
Approved On: _____ Approved By: _____

ISO Monorail Track Head

By Visual Comfort Architectural



Description

ISO Monorail Track Head is compatible with 1-circuit Monorail track systems. Includes 12 volt, 16 watt field replaceable LED module. Features 20, 30 or 50 degree beam spread options and four stem length options. Available with 80 or 90 CRI. Includes Freejack and Monorail connector. As a general rule when using the ISO head, it is not recommended using greater than 33 percent of the maximum wattage for the low voltage transformer due to the inrush current requirements. Dimmer type dependent on system transformer (low voltage magnetic or electronic). Note: 2700K fixtures are not available with 90 CRI.

Specifications


COLOR	N/A
BODY FINISH	White
WATTAGE	16W
DIMMER	N/A
DIMENSIONS	18"L x 2.8"W x 3.6"H
INTEGRATED LED MODULE	1 x LED/16W/12V LED

Technical Information

BEAM ANGLE	50°
COLOR RENDERING	90 CRI
LAMP COLOR	3000K
LUMENS/WATT	44.00
LUMINOUS FLUX	704 lumens



Shown in white



CLICK TO VIEW PRODUCT

Notes: