

Lightology

lightology.com
866-954-4489
04-02-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG967359**
 Approved On: _____ Approved By: _____

TruTrack Dual Source Recessed Track 24VDC By PureEdge Lighting



Description


TruTrack is a 24VDC 2-circuit recessed track and linear plaster-in LED system (one circuit for track, second circuit for LED strip) designed for combining recessed track spots and LED strip for a clean modern look. The linear plaster-in LED system is only 5/8 inch thick, eliminating concern of hitting studs or joists and allowing complete flexibility to make turns along ceilings and walls. TruTrack can be installed on a single surface (wall or ceiling), or on multiple surfaces going from the wall to the ceiling. TruTrack channel is available in 2, 4, 6, and 8 foot field-cutable lengths. LED strip is sold in 1 foot increments up to 40 foot maximum length, up to 96 watts before re-feeding. Track head lumen output up to 1256 lumens with multiple fixed and adjustable beam spread options (track heads sold separately). Track includes two white plastic opaque slot covers to protect the inside of the track during the installation process and one transparent lens slot cover to diffuse the output of the integrated LED strip. Required 24VDC remote Universal power supply (two required for 2-circuit), Power Feed(s) (End, Center, L, T or X), Track Heads, LED 2-Pin 6 Amp Stomp Strip, Dead End Cap(s) (TR24-CA), and optional mounting and pre-formed accessories, sold separately. Note: Contact salesperson for more information on LED Stomp Strip. System may be switched and dimmed as a 1-circuit or separately as a 2-circuit system. Remote power supply can be located up to 40 feet away from the power feed. Product is built to order

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	24"L x 2.59"W x 0.63"H
BULB	N/A



Shown in white



CLICK TO VIEW PRODUCT

Notes: