

# Lightology

lightology.com  
866-954-4489  
06-18-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **DLS969789**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Excel 4 Inch Round Recessed Panel Light By DALS Lighting



### Description

The Excel 4 Inch Round Recessed Panel Light features sleek, low-profile aluminum construction that is both stylish and practical for indoor and outdoor settings. Installation is easy, and the fixture can be daisy chained. Using edge-lit technology, LED light diffused by a frosted lens provides a smooth 360 degree wide spread of ambient illumination. Dimmable with most TRIAC dimmers (see attached manufacturer dimmer reference). Optional accessories sold separately. Color temperature options: CCT Select: The light can be set to 2700K, 3000K, 3500K, 4000K, or 5000K using a switch on the panel wire. 3000K Warm Dim: The light warms from 3000K to 2200K as it is dimmed, mimicking incandescent light. A junction box with an integrated driver is included. Note: Warm dim is only available with the White finish.

### Specifications

COLOR . . . . . Frosted  
BODY FINISH . . . . . Satin Nickel  
WATTAGE . . . . . 11W  
DIMMER . . . . . Standard 120V  
DIMENSIONS . . . . . 4.75"W x 0.5"H  
INTEGRATED LED MODULE . . . . . 1 x LED/11W/120V LED  
COUNTRY OF ORIGIN . . . . . China

### Technical Information

APERTURE SHAPE . . . . . Round  
HOUSING HEIGHT . . . . . 2"  
HOUSING TYPE . . . . . Remodel IC Airtight  
CEILING TYPE . . . . . Drywall with Trim  
FUNCTION . . . . . Downlight  
LAMP LIFE . . . . . 35000 hours  
BEAM ANGLE . . . . . 110°  
BEAM SPREAD . . . . . Wide flood  
COLOR RENDERING . . . . . 80 CRI  
LAMP COLOR . . . . . CCT Select  
LUMENS/WATT . . . . . 72.73  
LUMINOUS FLUX . . . . . 800 lumens



Shown in satin nickel / frosted



CLICK TO VIEW PRODUCT

Notes: