

lightology.com 866-954-4489 07-28-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: ELE969919	
Approved On:	Approved By:

Entra CL 3IN Square Flangeless New Construction Housing By Visual Comfort Architectural











Description

This Entra CL new construction housing is designed for use with an Entra CL 3 inch square flangeless trim. The housing includes a Universal 120-277V driver, dimmable by standard reverse-phase, forward-phase, TRIAC, or 0-10V dimming (down to 5%). 277V is only compatible with 0-10V dimming. Damp-rated when used with an adjustable trim, wet-rated when used with a fixed downlight or wall wash trim. Notes: A complete fixture requires this housing and a trim, sold separately. The light module is included with the trim. The 15W housing is not compatible with a warm dim trim.



Shown in galvanized steel



Specifications

REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
BUILB NOT INCLUDED 1 x L ED/12W/120-277V L ED

Technical Information

APERTURE SHAPE
HOUSING HEIGHT
HOUSING TYPE New construction IC Airtight
${\sf CEILINGTYPE} \ \ldots \ \ldots \ \ldots \ \ldots \ . \ . \ . \ . \ . \ .$
LUMENS/WATT
LUMINOUS FLUX



CLICK TO VIEW PRODUCT

Notes:				
--------	--	--	--	--