

lightology.com 866-954-4489 07-02-25

| Project: | |
|--------------------------|---------------|
| Company: | |
| Location: | Fixture Type: |
| SPEC #: EDG972948 | |
| Approved On: | Approved By: |
| | |

Lazer Line Static White Up or Down Suspended System 24VDC By PureEdge Lighting







Description

Lazer Line is a 24VDC direct or indirect (uplight or downlight) LED lighting system providing general illumination for architectural applications. The fieldcuttable single channel in 3 and 5 watts per foot is sold in 1 inch increments and allows a maximum length of 30 feet (3 watt) or 20 feet (5 watt) with power feed at one end and one non-power turnbuckle, or a maximum length of 60 feet (3 watt) or 40 feet (5 watt) with power feed turnbuckles at both ends. The 4 inch round turnbuckles allow Lazer Line to be positioned 0-90 degrees relative to the mounting surface, creating a 3-dimensional appearance. Mounts to standard 4 inch square junction box with round plaster ring. Paint canopy to blend into wall for a seamless look. Note: System includes Lazer Line channel and mounting hardware. System requires a Universal remote power supply (dimmable TRIAC/ ELV/0-10V), sold separately. Product is built to order.


Specifications

| COLOR |
|-------------------------------|
| BODY FINISH |
| WATTAGE |
| DIMMER Low Voltage Electronic |
| DIMENSIONS |
| INTECDATED LED MODILLE |

Technical Information

| LAMP LIFE | |
|-----------------|--|
| BEAM ANGLE | |
| COLOR RENDERING | |
| LAMP COLOR | |
| LUMENS/WATT | |
| LUMINOUS FLUX | |





Notes: